



**Software Forensics for Discriminating between
Program Authors using Case-Based Reasoning,
Feed-Forward Neural Networks and Multiple
Discriminant Analysis**

Stephen MacDonell
Andrew Gray
Grant MacLennan
Philip Sallis

**The Information Science
Discussion Paper Series**

Number 99/12
June 1999
ISSN 1177-455X

University of Otago

Department of Information Science

The Department of Information Science is one of six departments that make up the Division of Commerce at the University of Otago. The department offers courses of study leading to a major in Information Science within the BCom, BA and BSc degrees. In addition to undergraduate teaching, the department is also strongly involved in postgraduate research programmes leading to MCom, MA, MSc and PhD degrees. Research projects in spatial information processing, connectionist-based information systems, software engineering and software development, information engineering and database, software metrics, distributed information systems, multimedia information systems and information systems security are particularly well supported.

The views expressed in this paper are not necessarily those of the department as a whole. The accuracy of the information presented in this paper is the sole responsibility of the authors.

Copyright

Copyright remains with the authors. Permission to copy for research or teaching purposes is granted on the condition that the authors and the Series are given due acknowledgment. Reproduction in any form for purposes other than research or teaching is forbidden unless prior written permission has been obtained from the authors.

Correspondence

This paper represents work to date and may not necessarily form the basis for the authors' final conclusions relating to this topic. It is likely, however, that the paper will appear in some form in a journal or in conference proceedings in the near future. The authors would be pleased to receive correspondence in connection with any of the issues raised in this paper, or for subsequent publication details. Please write directly to the authors at the address provided below. (Details of final journal/conference publication venues for these papers are also provided on the Department's publications web pages: <http://divcom.otago.ac.nz:800/COM/INFOSCI/Publctns/home.htm>). Any other correspondence concerning the Series should be sent to the DPS Coordinator.

Department of Information Science
University of Otago
P O Box 56
Dunedin
NEW ZEALAND

Fax: +64 3 479 8311
email: dps@infoscience.otago.ac.nz
www: <http://divcom.otago.ac.nz:800/COM/INFOSCI/>

Software Forensics for Discriminating between Program Authors using Case-Based Reasoning, Feed-Forward Neural Networks and Multiple Discriminant Analysis

Stephen G. MacDonell, Andrew R. Gray, Grant MacLennan, and Philip Sallis

Department of Information Science

University of Otago

PO Box 56, Dunedin, New Zealand

+64 3 4798135 (phone) +64 3 4798311 (fax)

stevemac@infoscience.otago.ac.nz

Abstract

Software forensics is a research field that, by treating pieces of program source code as linguistically and stylistically analyzable entities, attempts to investigate aspects of computer program authorship. This can be performed with the goal of identification, discrimination, or characterization of authors. In this paper we extract a set of 26 standard authorship metrics from 351 programs by 7 different authors. The use of feed-forward neural networks, multiple discriminant analysis, and case-based reasoning is then investigated in terms of classification accuracy for the authors on both training and testing samples. The first two techniques produce remarkably similar results, with the best results coming from the case-based reasoning models. All techniques have high prediction accuracy rates, supporting the feasibility of the task of discriminating program authors based on source-code measurements.

1 Introduction

In a surprisingly large number of situations there is a need to investigate the nature of a computer program's authorship. By this it is meant, that there is some question concerning the authorship of a series of programs or alternatively the characteristics of program authors [3].

The most widely known example is plagiarism detection in an academic setting where students' assignments can be compared to see if some are "suspiciously similar" [7]. The incidence of highly similar programs can provide suggestive evidence that one student's code may have been derived from another's. This particular area of research provided the origins of the ideas that now make up the field of software forensics – which is defined here as the study of program characteristics

with the intention of identifying, examining, or discriminating between program authors [1].

Software forensics also includes the areas of authorship characterization, as in psychological studies of the relationship between programmer attributes and their code and between programming conditions and code. The analysis of malicious code (such as computer viruses, software trapdoors, and trojan horses) is another application area, although this involves more subjective analysis [6]. Other applications of software forensics include quality control (through coding standards for example, cyclomatic complexity or comment density which can be used as an indicator of internal documentation quality), author tracking (for example, determining the author of code of unknown origin), change control (tracking the authorship of changes and quality control when making changes), and ownership disputes.

While the idea of dissenting the structure and nature of programs to discern some information about the likely author or authors and/or their characteristics may appear somewhat esoteric, perhaps even unrealistic, it has been shown that such activities are feasible, at least under certain circumstances [2]. In fact many measurements can be difficult for programmers to change [6]. An open question is how such models should be constructed to best represent the mappings between program features, authors, and the authors' characteristics.

In this paper the focus will be on the area of developing models that are capable of discriminating between several authors using source-code based measurements. The measurements that are preferred here are those that can be automatically extracted from source code by pattern matching algorithms since the volumes of data needed for these applications will generally surpass convenient human measurement. Applications for such authorship discrimination procedures

include plagiarism detection, ownership disputes, and the psychological study of programmers.

2 Techniques for authorship discrimination

2.1 Neural networks

There are a vast number of neural network architectures and training algorithms contained within the literature. The most commonly used architecture for most applications is that of a feed-forward neural network (FFNN), which is still generally trained using some form of the back-propagation algorithm.

The main issues when using this approach concern selecting the optimal architecture for the network and in stopping the training (usually by using data set splitting and stopping training when a validation data set error is minimized). The use of data set splitting can be seen as a disadvantage, since this reduces the amount of data available for the network to learn the relationships.

More sophisticated approaches that do not require hold-out samples are not investigated here as they are likely to be less accessible to researchers in applied fields.

2.2 Discriminant analysis

Multiple discriminant analysis (MDA) is a statistical technique that separates observations into two or more groups based on several orthogonal linear functions of the independent variables. The technique assumes a reasonable degree of multivariate normality, with logistic regression an alternative where this is not the case. However ordinary logistic regression is more suited to binary outcomes, and will not be discussed further here.

A significant advantage of discriminant analysis as a technique is the easy availability of stepwise procedures for controlling the entry and removal of variables. By working with only those necessary variables we increase the chance of the model being able to generalize to new sets of data. In addition, the data collection costs can be reduced, sometimes significantly, by working with a smaller set of variables.

Another advantage of the technique is that it provides probability information for the predictions, both in terms of the conditional probability of an observation belonging to a particular class given its classification and the conditional probability that a particular observation will be classified as belonging to a particular class given its real class. In a legal setting such information would certainly be required if software forensic results were to be accepted as evidence.

2.3 Case-based reasoning

Case-based reasoning (CBR) is a method for modeling the relationship between a series of independent variables and one or more dependent variables by storing the cases (observations) in a database. When presented with a new observation, the cases that are similar in terms of the independent variables are retrieved and the dependent variables calculated from them using some form of “averaging” process.

CBR has the advantages of not requiring any distributional assumptions *per se* but does require the specification of a distance metric (for finding the closest exemplars to the presented case and calculating their similarity). Scaling (if any is used) when measuring similarity can be based on ranges or standardized values if some distributional assumptions are made. The other aspect that requires some thought is the selection of a method for combining the cases. Again, a simple weighted average approach can be used once the distance metric has been decided on, with perhaps some power of distance used to increase the influence of closer observations and reduce the influence of outliers. In most implementations a threshold of similarity or a limit of “related” cases is used to prevent all stored cases influencing all predictions.

One particular case-based reasoning system that has been previously used for software metric research is the ANGEL system [5]. ANGEL has also been implemented as part of the IDENTIFIED system that was used in this paper for the measurement extraction, and CBR and FFNN models [1, 4]. The ANGEL system also allows for the automatic selection of relevant variables (at some considerable computational cost), although here no attempt will be made to select any optimal subset of variables when using this technique.

3 Authorship data set

The data that we have chosen to illustrate the author discrimination problem exhibits many of the characteristics that present some of the most perplexing difficulties found when undertaking such analyses. The data contains programs from seven authors with widely varying amounts of data and from three basic source types. 26 measures were extracted for each program using the IDENTIFIED tool (Table 1).

All programs were written in standard C++. The source code for authors one, two, and three are from programming books; authors four, five, and six are experienced commercial programmers; and author seven’s code is from examples provided with a popular C++ compiler. The choice of program sources may appear unusual, but it was felt that the usual source of student programs was no more realistic.

Measurement	Description
WHITE	Proportion of lines that are blank
SPACE-1	Proportion of operators with whitespace on both sides
SPACE-2	Proportion of operators with whitespace on left side
SPACE-3	Proportion of operators with whitespace on right side
SPACE-4	Proportion of operators with whitespace on neither side
LOCCHARS	Mean number of characters per line
CAPS	Proportion of letters that are upper case
LOC	Non-whitespace lines of code
DEBUGSYM	Debug variables per line of code (LOC)
DEBUGPRN	Commented out debug print statements per LOC
COM	Proportion of LOC that are purely comment
INLCOM	Proportion of LOC that have inline comments
ENDCOM	Proportion of end-of-block braces labelled with comments
GOTO	Gotos per non-comment LOC (NCLOC)
COND-1	Number of #if per NCLOC
COND-2	Number of #elif per NCLOC
COND-3	Number of #ifdef per NCLOC
COND-4	Number of #ifndef per NCLOC
COND-5	Number of #else per NCLOC
COND-6	Number of #endif per NCLOC
COND	Conditional compilation keywords per NCLOC
CCN	McCabe's cyclomatic complexity number
DEC-IF	if statements per NCLOC
DEC-SWITCH	switch statements per NCLOC
DEC-WHILE	while statements per NCLOC
DEC	Decision statements per NCLOC

Table 1: The 26 variables used

For the purposes of testing the various models to be developed in §4.1, 4.2, and 4.3, the available data was split (as shown in Table 2) with stratification (as equally as possible) across authors. The split was approximately 25% in the Training 1 set, 25% in the Training 2 set, and 50% in the Testing set.

In some cases, especially for authors 4 and 5, very little data is available, but this can be seen as a useful test of a situation certain to arise in practice. The only concern here is that the prior probabilities from the Training set match the posterior probabilities in the Testing set. In a simulation-based study the use of resampling would appear a better choice to assess the techniques. However since this study involves only

one split of the data set, the use of stratification seems preferable to the increased effects of chance bought on by resampling.

4 Results

4.1 Neural network

The ultimately selected FFNN was a 26-9-7 network, with the logistic transfer for both hidden and output layers. The best network found was trained for 250 epochs using the backpropagation algorithm (learning rate 0.2, momentum 0.9). All 26 variables provided were used. Half of the training data (Training 1) was used for the

Data set	Author							Total
	1	2	3	4	5	6	7	
Training 1	17	29	7	3	1	11	21	89
Training 2/Validation	17	28	6	3	2	10	21	87
Testing	34	57	13	6	2	21	42	175
Total	68	114	26	12	5	42	84	351

Table 2: Data set splits

actual training, while the remainder (Training 2) was used to stop training and select the best architecture.

Table 3 shows the confusion matrix for the network's predictions on the testing set. Those programs that were correctly classified are shown as boxed entries on the main diagonal. As can be seen the network has a high classification rate of 81.1%. Authors two and three are obviously distinct from all others, while the small amount of data available for author five seems likely to be responsible for all of those programs being misclassified.

Since this technique was the only one that required splitting the training data, all other techniques were developed using both training data sets (Training 1 and 2) and just the first 50% (Training 1). The other modeling techniques when tuned using both training data sets could be expected to enjoy an advantage over the neural network model in terms of the greater number, and thus richness, of cases available. While in the second case the neural network models should have an advantage since they are tuned on the same data set whilst having their generalisability encouraged by the use of the validation set. §4.4 shows the performance of all models on all (sub)sets of data.

4.2 Multiple discriminant analysis

The MDA was a stepwise MDA (Wilk's lambda was used for entry and exit of variables). Prior probabilities were obtained from the data and within group covariance matrices were used. As discussed in §4.1 both sets of training data were used as part of the model parameter tuning since no model selection process was used. Another model was developed using only the Training 1 data set (50% of the training data). See §4.4 for these results.

Table 4 shows the confusion matrix for the predictions made on the with-held testing data. As with the neural network model the performance accuracy is 81.1% when using all training data. The patterns of confusion are similar for authors four, six, and seven but rather different for the other authors.

4.3 Case-based reasoning

The case-based reasoning model was developed using the ANGEL algorithm, with 5 analogies and weighted means for case aggregation. Tie resolution was also used. All variables were normalized in order to maintain a comparable scale.

All 26 variables were used, with two models developed – one using only 50% of the training data (Training 1) and another using all training data (Training 1 and 2). See §4.4 for a discussion of the performance of this reduced-data model.

Table 5 shows the confusion matrix for the testing data set. There is a considerably higher level of accuracy compared to the neural network and discriminant analysis models, with 88.0% accuracy achieved when using all training data.

4.4 Comparison

Table 6 shows the results for all five models developed. Note that the "training set" errors for the CBR models are leave-one-out since the case to be predicted should obviously not be in the training set. As can be seen the results for the FFNN and MDA models are quite remarkably almost identical (the FFNN and full-data MDA are in fact identical). However, each of these models made rather different patterns of confusion on all data sets.

The best performing technique in all cases is case-based reasoning. In terms of predictive performance on the test data set, its predictions were almost 7% better which appears to be a useful increase in performance. Even with the reduced training data set, the case-based reasoning model outperformed the neural network model by 5.2%.

This is suspected to be a result of the fact that programmers have more than one style of programming leading to several multi-dimensional "clouds" of points. Some sets of programs for a given programmer are apparently within other programmer's "clouds" of metrics, preventing simple explicit classification boundaries from properly classifying the systems.

5 Conclusions

The use of the proposed set of metrics for discriminating between seven authors shows promising results, especially when using the case-based reasoning technique. All techniques however provided accuracy between 81.1% and 88.0% on a holdout testing set would be certainly encouraging for the software forensics field as a whole.

It is tentatively suggested here that the nature of class boundaries for forensic applications is more amenable to modeling using case-based reasoning than partitioning approaches. The idea of multiple clusters suggests that other neural network architectures such as variants of LVQ could be fruitfully applied here.

We are now comparing the performance of different sets of forensic metrics, both structural and stylistic to determine which are the most useful in certain circumstances. Since stylistic metrics are easier to fake than structural, the ability of the latter to discriminate authorship is more useful.

Another area of interest is how each technique performs given certain quantities of data. Whilst the CBR

		Predicted author number							Total
		1	2	3	4	5	6	7	
Actual author number	1	20	1	6	1		1	5	34
	2		57						57
	3			13					13
	4		2		4				6
	5		2			0			2
	6	1	2	1			17		21
	7	4	3	4				31	42
Total		25	67	24	5	0	18	36	175

Table 3: Confusion matrix for testing data predictions from FFNN model using all training data

		Predicted author number							Total
		1	2	3	4	5	6	7	
Actual author number	1	26	1			3	1	3	34
	2	2	52		1		2		57
	3	1	2	10					13
	4		2		4				6
	5				1	0		1	2
	6	2	2	1			16		21
	7	3	3	2				34	42
Total		34	62	13	6	3	19	38	175

Table 4: Confusion matrix for testing data predictions from MDA model using all training data

		Predicted author number							Total
		1	2	3	4	5	6	7	
Actual author number	1	28	1	2				3	34
	2		57						57
	3			13					13
	4		2		4				6
	5		1			1			2
	6		5				16		21
	7	1	5	2	2			32	42
Total		29	71	17	6	1	16	35	175

Table 5: Confusion matrix for testing data predictions from CBR model using all training data

Model	Training 1	Training 2	Training 1 and 2	Testing
MDA (using 50% training)	98.9%	79.3%	89.2%	84.6%
MDA (using 100% training)	93.3%	85.1%	89.2%	81.1%
CBR (using 50% training)	87.6%	81.6%	84.7%	86.3%
CBR (using 100% training)	88.8%	80.6%	84.7%	88.0%
FFNN (using 100% training)	98.9%	79.3%	89.2%	81.1%

Table 6: Results for discriminating models

models were better here it would seem likely that their performance would suffer more from losing data when compared to models using actual classification boundaries.

References

- [1] A. Gray, P. Sallis, and S. MacDonell. Identified (integrated dictionary-based extraction of non-language-dependent token information for forensic identification, examination, and discrimination): A dictionary-based system for extracting source code metrics for software forensics. In *Proceedings of SE:E&P'98 (Software Engineering: Education and Practice Conference)*, pages 252–259. IEEE Computer Society Press, 1998.
- [2] I. Krsul and E. H. Spafford. Authorship analysis: Identifying the author of a program. *Computers & Security*, 16(3):233–256, 1997.
- [3] P. Sallis, A. Aakjaer, and S. MacDonell. Software forensics: Old methods for a new science. In *Proceedings of SE:E&P'96 (Software Engineering: Education and Practice)*, pages 367–371. IEEE Computer Society Press, 1996.
- [4] P. Sallis, S. MacDonell, G. MacLennan, A. Gray, and R. Kilgour. Identified: Software authorship analysis with case-based reasoning. In *Proceedings of the Addendum Session of the 1997 International Conference on Neural Information Processing and Intelligent Information Systems*, pages 53–56, 1998.
- [5] M. Shepperd and C. Schofield. Estimating software project effort using analogies. *IEEE Transactions on Software Engineering*, 23(11):736–743, 1997.
- [6] E. H. Spafford and S. A. Weeber. Software forensics: Can we track code to its authors? *Computers & Security*, 12:585–595, 1993.
- [7] G. Whale. Software metrics and plagiarism detection. *Journal of Systems and Software*, 13:131–138, 1990.